P772(L)

TOP DESIGN, GOOD ERGONOMICS 17" OFFICE SCREEN

The P772(L) is designed to bring to market a versatile and durable office product. People are becoming more and more aware of ecological, ergonomical and energy saving issues. CTX has incorporated the 3E Concern concept into this 17" monitor.

Special attention has been paid to the ergonomics of the P772. The monitor is height adjustable, easy to swivel, tilt and pivot due to the new mechanical engine, without compromising the appearance of the screen.

The P772(L) is ecologically sound, certified with TCO'03, TUV/GS and ISO13406-2.

Finally the monitor offers a more elegant, sleek and modern finish.

Size	17" diagonal viewable size
Type	Active Matrix TN-TFT LCD
Resolution	1280 x 1024 array matrix
Colours	16 million colors
Pixel Pitch	0.264 mm / 0.264 mm pixel pitch
Contrast Ratio	500:1, Typical
Average Surface Brightness	260 nit (cd/m²), Typical
Horizontal Viewing Angle (CR:10)	140°
Vertical Viewing Angle (CR:10)	140°
Response Time	16 ms, Typical
Horizontal Scan	30kHz ~ 80kHz
Vertical Refresh	59Hz ~ 75Hz
Plug & Play	VESA DDC 2B (VGA) / DDC 2B+ (DVI) Standard
Input Signals	RGB: Analog, 0.0 ~ 0.7 V Peak to Peak, DVI: TMDS
	Sync. Signal: Separate 3.3V and 5V TTL H/V Sync.
Input Connection (Detachable)	VGA 15 pin D-Sub & DVI-D (P772)
Speakers	Stereo, 1 W x 2, with Amplifier
User Controls and Indicator	Front Panel Controls:
	Power Switch, LED Indicator, ESC, Up, Down, Enter
Security Key Lock	Yes
VESA Wall Mount Compatible	Yes (100 mm)
Vertical Lift Adjustment	Yes
Monitor Tilt (Forward / Backward)	Yes
Monitor Pan Swivel (Left / Right)	Yes
Portrait / Landscape Pivot	Yes
Power Supply	Built-In Power Supply
Input	Universal AC 100~240V (50~60Hz)
Power Consumption	39 W (max.)
Off Mode (Power Saving Status)	2 W
Power Off	1 W
Safety Regulations	CE, UL, CUL, FCC, TUV/GS, ISO13406-2, TCO'03

SEE MORE DETAILS

www.ctxeurope.com

CTX

COMMITTED TO XCELLENCE

3E Concern